


Operating Instructions



35ft Metal Reel with 13W Fluorescent Pro Work Light

Model 94301



 This is the safety alert symbol. It is used to alert you to potential personal injury hazards. Obey all safety messages that follow this symbol to avoid possible injury or death.

Save these instructions. For your safety, read understand, and follow the information provided before attempting to use. Use and repair of this product may require special skills and knowledge. Instructions and safety information shall be conveyed in the operator's language before use of this product is authorized. If any doubt exists as to the safe and proper use of this spotlight, remove from service immediately. **Inspect before each use.** Do not use if broken or damaged parts are noted. Immediately remove from service when the spotlight operates abnormally or appears damaged in any way.

WARNING

- Read, understand, and follow all printed materials provided with/on this device before use.
- Do not shine light into eyes.
- This light is not recommended for use by children. Keep out of reach of children.
- Do not alter or modify this product.
- Failure to heed these markings may result in personal injury and/or property damage.

California Proposition 65 Warning

The electrical cord on this product contains chemicals, including lead, known in the state of California to cause birth defects and reproductive harm. **Wash hands thoroughly after handling!**

SPECIAL FEATURES

- 35 ft 16/3 SJTOW heavy duty cord is flexible in cold weather and resistant to both oil and water
- Steel housing reel
- Hardware included for wall or ceiling mounting
- 13 Watt bright fluorescent bulb
- 360° ratcheting hook and dual metal hooks allow for hanging from either end
- On-off switch and one outlet built into handle
- Top lens focuses light for precision lighting needs
- Shatter proof lens and high impact design
- Overload protection on reel and light



WARNING

- Fully insert plug to reduce the risk of electric shock.
- Do not operate without lens in place.
- Always unplug when not in use.
- Disconnect power before installing or servicing.
- Keep out of reach of children.
- Do not try to plug in when hands are wet or damp, or if standing on a wet or damp surface, or in water.
- This unit is not waterproof and is intended for general use indoors. Do not use in potentially dangerous locations, such as in flammable or explosive atmospheres.

INSTALLATION

Ceiling Mount - 360° Rotation

1. Select location within 2 feet of an electrical outlet.
2. Screw the Hanger Hook into the ceiling.
3. Hang Reel on Hook.
4. Close Hook with pliers to prevent Reel from coming off.
5. Adjust Ball Stop so light hangs at desired length when cord is retracted.

Optional Wall Mount – 180° Rotation

1. Select location within 2 feet of an electrical outlet.
2. Take U Shaped Bracket and attach to wall with the screws provided.
3. Place Hanger Bracket inside U shaped Bracket lining up small holes in the Brackets.
4. Insert Locking Pin through lined-up holes.
5. Adjust Ball Stop so light hangs at desired length when cord is retracted.

OPERATING INSTRUCTIONS

1. Pull entire length of cord from reel, and then plug into any 110-125V, 3 conductor outlet.

Note: This product has a 3-prong grounded electrical plug. The plug must be used with an outlet that is properly installed and grounded in accordance with local codes and ordinances. If using an extension cord, make sure it is the proper configuration for a grounded connection.

2. Depress switch in handle to turn light on/off.
3. To operate Reel pull cord out to desired length and stop. If cord does not hold, continue to pull cord slowly, stopping every four inches. This will engage lock. To retract pull cord out 2 to 4 inches and guide the cord slowly back into the reel.
4. Keep cord clean to assure smoothest automatic retraction.
5. Do not allow the cord to retract unrestricted back into reel.

BULB REPLACEMENT INSTRUCTIONS

1. Remove power supply plug from outlet.
2. Remove end bumper and end cap.
3. Remove bulb protector, grasp end of bulb and pull straight out.
4. Slide in new bulb and pull down into socket.
5. Re-assemble the bulb protector, the end cap and the end bumper.

1 YEAR LIMITED WARRANTY

For a period of one (1) year from date of purchase, SFA Companies will repair or replace, at its option, without charge, any of its products which fails due to a defect in material or workmanship under normal usage. This limited warranty is a consumer's exclusive remedy.

Performance of any obligation under this warranty may be obtained by returning the warranted product, freight prepaid, to SFA Companies Warranty Service Department, 10939 N. Pomona Ave., Kansas City, MO 64153.

Except where such limitations and exclusions are specifically prohibited by applicable law, (1) THE CONSUMER'S SOLE AND EXCLUSIVE REMEDY SHALL BE THE REPAIR OR REPLACEMENT OF DEFECTIVE PRODUCTS AS DESCRIBED ABOVE. (2) SFA Companies SHALL NOT BE LIABLE FOR ANY CONSEQUENTIAL OR INCIDENTAL DAMAGE OR LOSS WHATSOEVER. (3) ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, SHALL BE LIMITED TO NINETY DAYS, OTHERWISE THE REPAIR, REPLACEMENT OR REFUND AS PROVIDED UNDER THIS EXPRESS LIMITED WARRANTY IS THE EXCLUSIVE REMEDY OF THE CONSUMER, AND IS PROVIDED IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED. (4) ANY MODIFICATION, ALTERATION, ABUSE, UNAUTHORIZED SERVICE OR ORNAMENTAL DESIGN VOIDS THIS WARRANTY AND IS NOT COVERED BY THIS WARRANTY.

Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

