



AIR ACTUATED FOOT PUMPS

- User friendly foot-actuated design for easy control of moving fluid at tremendous rate
- Uses 3/8" NPTF fluid coupler
- Efficiently operates many industrial and construction single-acting ram applications
- Provides up to 10,000 PSI with standard shop air supply of 110-175 PSI
- A compact yet powerful Air Turbo Motor, U.S. Patent No. 5,341,723 is equipped to raise the load to the desired height efficiently, effortlessly, and safely
- U.S. Patent No. 5,946,912, a built-in by-pass device protects hydraulic system from over pumping damage
- Made of durable light weight corrosion-free aluminum
- 22903B is equipped with mounting holes and mounting hardware for repetitive use applications



22905
122 in³ Usable oil



22903
91.5 in³ Usable oil

| Model | Usable Oil Capacity | Pressure Rating | Air Pressure Rating | Output Flow Rate | | G.W. |
|--------|----------------------|-----------------|---------------------|--------------------------|--------------------------|---------|
| | | | | No Load | Load | |
| 22903 | 91.5 in ³ | 10,000 PSI | 110-175 PSI | 66 in ³ /min. | 11 in ³ /min. | 20 Lbs. |
| 22903B | 91.5 in ³ | | | 66 in ³ /min. | 11 in ³ /min. | 20 Lbs. |
| 22905 | 122 in ³ | | | 65 in ³ /min. | 12 in ³ /min. | 22 Lbs. |