# AIR ACTUATED FOOT PUMPS

- User friendly foot-actuated design for easy control of moving fluid at tremendous rate
- Uses 3/8″ NPTF fluid coupler
- Efficiently operates many industrial and construction single-acting ram applications
- Provides up to 10,000 PSI with standard shop air supply of 110-175 PSI
- A compact yet powerful Air Turbo Motor, U.S.Patent No.5,341,723 is equipped to raise the load to the desired height efficiently, effortlessly, and safely
- U.S. Patent No.5,946,912, a built-in by-pass device protects hydraulic system from over pumping damage
- Made of durable light weight corrosion-free aluminum
- 22903B is equipped with mounting holes and mounting hardware for repetitive use applications




22905
122 in³ Usable oil



22903
91.5 in³ Usable oil

| Model | Usable Oil Capacity | Pressure Rating | Air Pressure Rating | Output Flow Rate | | G.W. |
|---|---|---|---|---|---|---|
| | | | | No Load | Load | |
| **22903** | 91.5 in³ | 10,000 PSI | 110-175 PSI | 66 in³/min. | 11 in³/min. | 20 Lbs. |
| **22903B** | 91.5 in³ | | | 66 in³/min. | 11 in³/min. | 20 Lbs. |
| **22905** | 122 in³ | | | 65 in³/min. | 12 in³/min. | 22 Lbs. |