



## GAS PUMP with SOLENOID VALVE and HONDA ENGINE

- Gas engine pump will provide 10,000 psi. hydraulic force at remote locations
- Industrial grade 10.2 hp Honda gas engine
- · Ideal for applications when a remote control is required
- Two speed pump designed for rapid cylinder advance
- Gas pump features a sturdy protective roll cage for use in the toughest environments







BUILT TO LAST

Motor Size (hp)	Usable Oil Capacity (gal)	Model	Max. Pressure	Pressure Rating (psi)		Mahar Tara	Valve	Rotation	Sound	Weight
		Number	Output (psi)	1st Stage	2nd Stage	Valve Type	Function	Speed (rpm)	Level (dBA)	(lbs)
10.2	5	PGSL1005	10,000	700	10,000	3 way, 3 position	Advance/ Hold/ Return	3,600	93	194
10.2	5	PGSML1005	10,000	700	10,000	4 way, 3 position	Advance/ Hold/ Return	3,600	93	194
10.2	10	PGSL1010	10,000	700	10,000	3 way, 3 position	Advance/ Hold/ Return	3,600	93	223
10.2	10	PGSML1010	10,000	700	10,000	4 way, 3 position	Advance/ Hold/ Return	3,600	93	223
10.2	15	PGSL1015	10,000	700	10,000	3 way, 3 position	Advance/ Hold/ Return	3,600	93	252
10.2	15	PGSML1015	10,000	700	10,000	4 way, 3 position	Advance/ Hold/ Return	3,600	93	252

Oil Output Flow Rate		Model	Dimensions (in)							
PSI	In³/Min.		Number	А	в	с	D	E	F	G
no load	1,070	1.E.	PGSL1005	26.57	21.5	20.94	10.47	11.50	12.43	15.47
1,000	592		PGSML1005	26.57	21.5	20.94	10.47	11.50	12.43	18.74
5,000	256		PGSL1010	28.25	23.37	27	13.5	12	12.93	17.375
10,000	200		PGSML1010	28.5	23.37	27	13.5	12	12.93	19.765
			PGSL1015	28.25	23.37	27	13.5	12	12.93	17.375
		and the	PGSML1015	28.25	23.37	27	13.5	12	12.93	19.765

## INDUSTRIAL HYDRAULIC EQUIPMENT

## 1-888-332-6419 www.bvahydraulics.com