

## TOE JACKS

- Heat treated and chrome plated medium-carbon steel cylinder
- Chrome plated rod promotes longer seal life and optimum performance
- U.S. Patented by-pass device protects hydraulic system from over traveling damage
- Hydraulic system is protected from internal damage by a patented by-pass mechanism, U.S. Patent No.5,946,912



| Capacity<br>(tons) | Model<br>Number | Toe Saddle          |                     | Head Saddle         |                     | Hydraulic<br>Lifting<br>(in) | Base Size<br>(L x W)<br>(in) | Weight<br>(lbs) |
|--------------------|-----------------|---------------------|---------------------|---------------------|---------------------|------------------------------|------------------------------|-----------------|
|                    |                 | Min. Height<br>(in) | Max. Height<br>(in) | Min. Height<br>(in) | Max. Height<br>(in) |                              |                              |                 |
| 3                  | J13060          | 0.62                | 5.75                | 9.0                 | 14.12               | 5.12                         | 6.00 x 4.37                  | 36.1            |
| 6                  | J13120          | 0.88                | 6.00                | 10.50               | 15.63               | 5.13                         | 11.00 x 7.50                 | 55.0            |
| 10                 | J13200          | 1.13                | 6.25                | 11.00               | 16.13               | 5.13                         | 11.63 x 9.00                 | 84.0            |
| 15                 | J13300          | 1.13                | 6.63                | 13.13               | 18.63               | 5.50                         | 12.50 x 10.75                | 116.6           |