SFA C-1000(Pro-lift) stick on plastic shrink wrap(front) Size: 8.5”(W) x 11”(H)

CMYK

SFA C-1000(Pro-lift) stick on plastic shrink wrap(back) Size: 8.5”(W) x 11”(H)

Save these instructions. For your safety, read, understand, and follow the information provided with and on the foldable mechanic pad. The owner and operator of this pad shall have an understanding of safe operating procedures before attempting to use. The owner and operator of this device shall be aware that the use and care of this device may require special skills and knowledge. Instructions and safety information shall be conveyed in the operators native language before use of this product is authorized. If any doubt exists as to the safe and proper use of this foldable mechanic pad, remove from service immediately.

Inspect before each use. Do not use the device if cracked or damaged parts are noted. foldable mechanic pad that appears damaged in any way or operates abnormally shall be removed from service immediately until checked by qualified personnel. There are no replacement parts available for this device.

Product Description
This ProLift foldable mechanic pad is designed to provide the mechanic or inspector a stationary, stable and comfortable platform on which to lay and perform repair and/or inspection duties and represents the only authorized use of this product.

This foldable mechanic pad is designed for intermittent use on clean, smooth, dry, level surfaces. Although the foldable mechanic pad cover is water resistant, it is not waterproof and should never be used in standing water, in the rain or snow. Additionally, the foldable mechanic pad cover is not chemical resistant and should never be exposed to any driveway and garage chemicals such as gasoline, turpentine, motor oil, grease, degreasers, detergents, etc.

How to use
Determine that the application and environment are suitable for this device. Unfold the foldable mechanic pad and lay the side containing the velcro fasteners down on a clean, smooth, and level surface.

Carefully, gently lay upon the foldable mechanic pad. When done, wipe foldable mechanic pad with a clean damp cloth. When foldable mechanic pad cover is thoroughly dry, fold the foldable mechanic pad together at its seam, securing the foldable mechanic pad by pressing the velcro fasteners together.

Cleaning and Maintenance
No maintenance of this product is necessary beyond wiping clean with a clean, damp cloth. After the pad cover is dry, fold and store in a cool, clean, dry environment. Do not store this device near flame, caustic chemicals, or in direct sunlight. Do Not apply wax, household cleaners or other chemicals to this product.

⚠ WARNING

- Before using this device, read, understand, and follow all printed materials provided.
- DO NOT use in close proximity to gasoline, propane or natural gas, etc. This device is not suitable for use in explosive and/or combustible environments or when static discharge must be controlled.
- DO NOT expose to caustic chemicals or common garage, household chemicals.
- DO NOT expose to fire or high heat (+125°F).
- DO NOT use as a flotation device.
- DO NOT fall on or jump on this mechanic’s working mat.
- DO NOT alter, modify this product or use for a purpose other than its intended use.
- Use only on hard, level, dry and clean surfaces.
- Before using under a lifted load, ensure load is supported by appropriately rated jack stands.
- Keep out of the reach of children.
- Failure to heed these markings may result in personal injury and/or property damage.

Shinn Fu Company of America, Inc.
10939 N. Pomona Avenue
Kansas City, Missouri 64153
Tel.(816)891-6390 Fax.(816)891-6599
WWW.shinnfuamerica.com
Email: sfakc@shinnfuamerica.com

K Pantone 152C